

GE1000S-NG

Natural Gas Genset

Main configuration and features:

- Highly efficient gas engine
- AC synchronous alternator
- Gas safety train and gas protection device against leakage
- Cooling system suitable for ambient temperature up to 50°C
- Advanced engine control system, including: ignition system, detonation control system, speed control system, air/fuel ratio control system and cylinder temp. protection system
- Strict shop test for all gensets
- Able to be used directly outdoors with durable and firm characteristics and design against rain and dust
- Ventilation fan, electric inlet and outlet shutter
- Expansion tank and water jacket heater
- Industrial silencer with silencing ability of 12-20dB(A)
- Unattached switch cabinet and electric control cabinet
- Multi-functional control system with simple operation
- Data communication interfaces integrated into control system
- Lighting and smoke alarm system
- Monitoring battery voltage and charging automatically
- Auto refilling oil system
- Bus interface for connecting to higher level control unit



Electric data @50Hz

Voltage-V	Power-kW	Efficiency-%	Current-A
380	1000	38.0	1899
400	1000	38.0	1804
415	1000	38.0	1739
440	1000	38.0	1640

Soundproof canopy and control cabinet

Structure type	40 feet high-cube
Container painting	High-class paint
Electrical control cabinet	Integrated into container, IP54
Noise level@7m, dB(A)	84

Dimension and weight

Dimension (LxWxH), mm	12192X2438X2896
Weight, kg	23000

Special statement :

1. The technical data are based on natural gas with a lower calorific value of 34.71MJ/Nm³. The technical data indicated is based on standard conditions according to ISO8528/1, ISO3046/1 and BS5514/1.
2. The technical data is measured in standard conditions:
Absolute atmospheric pressure: 100kPa
Ambient temperature : 25°C
Relative air humidity : 30%
3. Rating adaptation at ambient conditions acc to DIN ISO 3046/1.
The tolerance for the specific fuel consumption is + 5 % at rated output.
4. Dimension and weight above are just for standard product, and may be subject to change. As this document is used only for presale reference, take the specification supplied by PowerLink before ordering as final.

Fuel and emission

Fuel type	Natural gas
Methane number	MN > 75
Excess air factor (Lambda)	1.7
NOx , mg/Nm ³	≤480
CO, mg/Nm ³	≤870
HCHO (formaldehyde) , mg/Nm ³	≤60
NMHC, mg/Nm ³	≤150
Fuel consumption @100% load, m ³ /h	273
Supply gas pressure range, kPa	25~35

Genset performance data and manufacturing technology

Genset model	GE1000S-NG	Telephone interference factor(TIF)	≤50
Electrical output power (kW)	1000	Telephone harmonious factor(THF)	≤2% , as per BS4999
Genset electrical efficiency	38.0 %	Manufacturing technology <ul style="list-style-type: none"> Special welded base frame, inner vibration isolators and design for whole lifting With high-class paint, enduring brightness as well resistance against abrasion and defacing Installation manual, operation and maintenance manual wiring program Standards and certificate <ul style="list-style-type: none"> ISO3046 , ISO8528 , GB2820 BS5000PT99 , AS1359 , IEC34 ISO9001:2008 quality system certification 	
Overload runtime at 1.1xSe(hour)	1		
Steady-state voltage deviation	≤±1%		
Transient-state voltage deviation	-15%~20%		
Voltage recovery time(s)	≤4		
Voltage unbalance	1%		
Steady-state frequency regulation	±0.5%		
Transient -state frequency regulation	±5%		
Frequency recovery time(s)	≤3		
Steady-state frequency band	0.5%		
Recovery time response(s)	0.5		

AC alternator performance data

Alternator brand	LEROY SOMER	Voltage	Power
Alternator model	LSA50.2M6	380V	1000 kW
Rated output power (kW)	1000	400V	1000 kW
Power factor	0.8	415V	1000 kW
Rated current @ 380V and 100% load (A)	1899	440V	952 kW
Excitation system	Brushless		
THF (BS EN60034- 1)	<2%		
Bearing number	2		
Winding material	100% copper		
Wiring connection	Star		
Rotor insulation class	H		
Winding pitch	2/3		
A.V.R. model	R450		
Voltage fluctuation(no load to full load)	± 0.5%		
Housing protection	IP23		
TIF (NEMA MG 1-22)	<50		
Excitation method	PMG		
Rated ambient temperature(°C)	40		
Rated stator temperature rise(°C)	125		

Efficient gas engine

General data

NO. of cylinders	16
Engine type	4-stroke, turbo charged and air to water cooled, lean burn
Cylinder arrangement	V-form , 60°
Bore x stroke	mm 160×190
Displacement	L 61.123
Compression ratio	12 : 1
Rated speed	rpm 1500
Rated output power	kW 1042
Excess air factor	1.7
Rotation direction	Anti-clockwise viewed on flywheel
Ignition timing	°BTDC 26

Cooling system

Total coolant capacity	L	95
Jacket water pressure in crankcase	kPa	≤100
Total coolant flow	L/min	950
Max. coolant exit temperature	°C	96
Max. coolant entry temperature	°C	81
Charge coolant flow	L/min	600
Charge coolant exit temperature	°C	40
Charge coolant entry temperature	°C	36
Coolant type	Mixture of 50% Inhibited ethylene glycol or propylene glycol and 50% clean fresh water. Lower ambient temp, higher content of antifreeze.	

Induction/exhaust system

Exhaust flow	m³/h	12632
Max. exhaust temp. before turbo	°C	600
Max. exhaust temp. after turbo	°C	468
Max. exhaust back pressure	mmH ₂ O	400
Max. suction restriction	mmH ₂ O	380
Exhaust outlet flange size	mm	2×152

Lubrication system

Total capacity	L	286
Sump maximum	L	257
Sump minimum	L	147
Oil temperature	°C	88
Oil pressure at rated speed	kPa	470
Oil flow - 1500rpm	L/min	402
Max. consumption	g/kWhr	0.25
Oil type	Single grade	
Oil pump	Gear driven	

Ignition system

Ignition type	Electronic ignition system
Polarity	Negative earth
Spark plug	Separate for every cylinder

Fuel consumption

100% load	m³/h	273
75% load	m³/h	210
50% load	m³/h	145



Fuel: Natural Gas - LHV = 34.71 MJ/m³

Fuel control system

Gas train, Including:	ball valves
	filters
	gas pressure gauge
	safety solenoid valves
	constant pressure regulator etc
	gas pressure relief valve

PCC-300 control system

Open control system is adopted with touch screen display , and various functions, including: engine protection and control, paralleling between gensets or gensets and mains, as well as communication functions, etc.



Main functions

- Engine monitor : coolant, lubrication, exhaust, battery
- Supply gas circuit monitor: pressure, temperature and CH4 content
- Auto paralleling and load share
- Voltage and PF control
- Alternator data : U, I, Hz, kW, kVA, kVar, PF, kWh, kVAh
- Mains data: U, I, Hz, kW, kVar, PF
- Modbus communication protocol based on RS232 and RS485 interfaces
- SMS message
- Internet connection and USB 2.0 interface
- 10-inch touch screen
- Internet monitor, auto orientation and cloud communication
- 1000 history events log

Advantages

- Accordant with consumer requirement
- Complete control project
- Convenient remote monitor and service
- Simplified engine start/stop control
- Enhanced stability and safety

Standard protection functions

Alternator protection

- 2xReverse power
- 2xOverload
- 4xOvercurrent
- 1xOvervoltage
- 1xUndervoltage
- 1xOver/underfrequency
- 1xUnbalanced current

Busbar/mains protection

- 1xOvervoltage
- 1xUndervoltage
- 1xOver/under frequency
- 1xPhase sequence
- 1xROCOF alarm

Standard control functions

Power control

- RPM control(synchronization)
- Power control(grid connection)
- Load share(island)

Valve control

- Cooling system

Fan control

- Ventilation for engine room
- Radiator fan

Engine protection

- Various routine and customized protection functions

Voltage control

- Voltage tracking (synchronization)
- Voltage control(island)
- PF control(grid connection)
- Reactive power share (island)

Pump control

- Cooling system

Lubrication control

- Auto refilling
- Warning and monitoring

- Monitoring

Standard configuration

Engine	Alternator	Canopy and base	Electrical cabinet
Gas engine Ignition system Lambda controller Electronic governor actuator Electrical start motor Battery system Auto charging system Detonation control system Cylinder temp. protection system Coupling	PMG AC alternator H class insulation IP23 protection AVR voltage regulator PF control	Steel monocoque base frame Engine bracket Vibration isolators Alternator base Soundproof canopy	Air circuit breaker Paralleling control system 10-inch touch screen Communication interfaces Electrical switch cabinet Lighting system Smoke alarm system Lightning protection
Gas supply system	Lubrication system	Standard voltage	Induction/ exhaust system
Gas safety train Gas leakage protection Air/fuel mixer	Oil filter Daily auxiliary oil tank Auto refilling oil system	380/220V 400/230V 415/240V 440/254V	Air filter Exhaust silencer Exhaust bellows Ventilation fan Electric inlet and outlet shutter
Cooling system	Service and documents		
Jacket water circulation pump Mixture circulation pump Jacket water radiator Mixture radiator Jacket water constant temp. valve Intercooler water constant temp. valve Jacket water heater Expansion tank	Tools package Installation and operation manual Maintenance manual Software manual Parts manual	Engine operation and maintenance manual Gas quality specification Control system manual After service guide Standard package	

Optional configuration

Engine	Alternator	Lubrication system
Heavy duty air filter Backfire safety control valve	Space heater AVR Treatments against humidity and corrosion	Oil consumption gauge New and used oil tank
Canopy and base	Gas supply system	Exhaust system
SECC base frame	Gas flow gauge	Guard shield from touch Residential silencer Three-way catalytic converter
Service and documents	Voltage	
Service tools Maintenance and service parts	220V 230V 240V	

Genset three view drawing

Note:

In the last three drawings, some components are hidden for showing purpose.

